

# SAFETY DATA SHEET



Advancing safety in all walks of life

Date of issue: 30/04/2007 revised  
Date printed: 30 april 2007

## 1. Identification of the substance/preparation and the company

GriP Base A 2030

**GriP® AntiSlip b.v, Rendementsweg 2H  
3641 SK MIJDRECHT, The Netherlands, Tel. +31 (0)297 526 166**

For other information, call Professional Motion Imaging General Services, tel. 01442 845945

## 2. Composition/information on ingredients

weight%	component	CAS-No.	EG Classification
1-5	butylglycol	111-76-2	Xn, R20/21/22-36/38
1-5	hydrocarbons	64771-71-7	Xn, R65-66

## 3. Hazards identification

## 4. First-Aid measures

**Skin:** Immediately flush with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.  
**Inhalation:** If symptomatic, move to fresh air. Get medical attention if symptoms persist.  
**Eyes:** In case of contact with eyes, flush immediately with plenty of water and seek medical attention.  
**Ingestion:** Do NOT induce vomiting. Give victim a glass of water. Get medical attention immediately. Never give anything by mouth to an unconscious person.

## 5. Fire-Fighting measures

**Extinguishing media:** Use appropriate medium for adjacent fire.  
**Special fire-fighting procedures:** Hazchem code 2T.  
**Special exposure hazards:** CO<sub>2</sub>, foam, dry powder; in cases of larger fires, water spray should be used.

## 6. Accidental release measures

Absorb spill with vermiculite or other inert material, such as sand or earth, then place in a suitable container and dispose via a licensed disposal contractor. Clean surface thoroughly to remove residual contamination.

## 7. Handling and storage

Personal precautionary measures: Do not get in eyes, on skin, on clothing. Use with adequate ventilation. Wash thoroughly after handling.

Prevention of fire and explosion: No special precautionary measures should be needed under anticipated conditions of use.

Storage: Cool conditions (5° - 20° C). Keep container closed. Keep away from incompatible substances. Storing: Not longer than 18 months.

Ventilation: Good general ventilation of 10 or more room volumes per hour in the work area is recommended. Match ventilation rates to conditions of use.

---

## 8. Exposure controls/personal protection

component	MAC-C
butylglycol	98 mg/m <sup>3</sup>
hydrocarbons	200 ppm

Respiratory protection: None should be needed. Wear a mask if necessary.

Eye protection: Wear safety glasses with side shields (or goggles) and a face shield.

Skin protection: Wear impervious gloves and protective clothing appropriate for the risk of exposure.

---

## 9. Physical and chemical properties

Physical form:	liquid
Colour:	milky white
Odour:	weak odour
Specific gravity:	1,157
Viscosity:	± 5500 mPa.s
Vapour pressure at 20° C.:	-
Volatile fraction by weight:	42,3-43,3%
Boiling point:	100 C.
Solubility in water:	miscible
pH:	ca. 8.0
Flash point:	65 gr. C.

---

## 10. Stability and reactivity

Stability:	-
Hazardous decomposition prod.:	-
Hazardous polymerization:	-

---

## 11. Toxicological information

Acute toxicity data:	no adverse effects have been encountered.
Effects of exposure:	-

---

## 12. Ecological information

The following properties are estimated from the components of the preparations.  
Do not allow to escape into waters, wastewater or soil.

